

Oil-heated and compact with the highest safety

## The therm C series

- Integrated trolley takes rough ground in its stride with large wheels with wide solid rubber tyres
- Integrated hose drum with foldable crank (option)
- 7.5 m power lead with cable reel (C 11/130: 5 m)
- One piece trigger gun with safety catch M2000 and lance with flat jet nozzle and flat jet nozzle
- Storage for trigger gun with safety catch and lance
- Shock absorbing buffers, front and rear
- Total-Stop system with delayed motor cut-out
- Additional electrical over-current protection
- Water flow monitoring
- Pre-aeration of combustion chamber
- Visual flame monitoring
- Safety thermostat triggers at emission temperatures above 230°
- 4-way safety system with overload protection
- Low fuel cut off for burner
- High pressure detergent
- Parking brake



therm C with hose drum



therm C without hose drum



Technical specifications	therm C 11/130	therm C 13/180	therm C 15/150
Ord. no. <b>with</b> hose drum / <b>without</b> hose drum	41,442 1 / 41,442	41,441 1 / 41,441	41,440 1 / 41,440
Operating pressure, continuously adjustable	30-130 bar / 3-13 MPa	30-180 bar / 3-18 MPa	30-150 bar / 3-15 MPa
Max. admissible overpressure	145 bar / 14,5 MPa	200 bar / 20 MPa	170 bar / 17 MPa
Water output	11 l/min (660 l/h)	13 l/min (780 l/h)	15 l/min (900 l/h)
Hot water output temperature (water supply 12 °C) continuously adjustable	12 - 80 °C	12 - 80 °C	12 - 80 °C
Steam level	max. 140 °C	max. 150 °C	max. 150 °C
Heating output	55 kW	60 kW	65 kW
Fuel tank capacity monitoring	25 l	25 l	25 l
Motor speed	1,400 rpm	1,400 rpm	1,400 rpm
Connected load	230 V, 15,0 A, 50 Hz	400 V, 8,7 A, 50 Hz	400 V, 8,7 A, 50 Hz
Power intake / Power output	3,4 kW / 2,3 kW	4,8 kW / 4,0 kW	4,8 kW / 4,0 kW
Weight with hose drum	179 kg	179 kg	179 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose, NW 8	15 m (44,879) / 10 m (44,878)	15 m (44,879) / 10 m (44,878)	15 m (44,879) / 10 m (44,878)
One piece trigger gun with safety catch M2000 with lance and flat jet nozzle	(12,486-D25045)	(12,486-D25045)	(12,486-D25055)
Water inlet filter	(13,310)	(13,310)	(13,310)